

Product Description:

ATF Dexron III is a high quality universal fluid to be used in automatic transmission, torque convertors and power steering of passenger car, light vans and commercial vehicles. ATF Dexron III is formulated on high refined premium quality hydrotreated base stock in combination with an unique additive package to reach the following properties.

ATF Dexron III is specifically engineered to help ensure long service life and to provide consistent shift performance for the life of the fluid, as well as better shift performance under extreme operating conditions. It is highly shear stable and has excellent oxidation resistance for long fluid life. It provides excellent antishudder performance and has excellent low-temperature properties for easier shifting in cold weather. The standards-viscosity fluid results in less frictional drag (churning loss) for improved transmission efficiency, thereby offering the potential for improved fuel economy performance.

DEXRON III ATF is formulated to meet and exceed of more specifications, including OEMs manufacturer specifications or recommended oils:

| | |
|-------------------|------------------|
| DEXRON III / IIIE | ALLISON C4 |
| FORD MERCON | CATERPILLAR TO-2 |

Typical Physical Characteristics

| PROPERTY TEST | UNITS | METHODS | RESULT |
|-----------------------------|-------|------------|------------|
| Viscosity Grade | | | Dexron III |
| Colour | | ASTM1500 | Red L5.0 |
| Density @ 15 °C | kg/m3 | | 0.84 |
| Kinematic Viscosity @ 40°C | cSt | ASTM D445 | 40.49 |
| Kinematic Viscosity @ 100°C | cSt | ASTM D445 | 7.31 |
| Viscosity Index | | ASTM D2270 | 146 |

These characteristics are typical of current product methods whilst future production will conform to ENZOIL Lubricants specifications, variations in these physical characteristics may occur.

Health & Safety Environment

- This product is unlikely to present any significant health and safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.
- Avoid contact with eyes and skin, use proper impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Protect the Environment

- Take used oil to an authorized collection point. Do not discharge used or new oil into drains, soil or water.

***Unparalleled Reliability
Performance And Peace Of Mind***

