

Product Description:

MOTORCYCLE OIL 2T is a high quality lubricant suitable for use in air cooled 2-stroke gasoline engines working under a wide variety of conditions and is formulated from premium quality hydrotreated base stocks and fortified with carefully selected high quality performance additives to provide engine protection and improved cleanliness in 2-stroke engines.

MOTORCYCLE OIL 2T offers excellent lubricity that protects against piston scuffing and premature wear of engine components. The low ash formulation effectively prevents preignition and spark plug fouling. The excellent miscibility with gasoline ensures stable homogeneous mixtures at low ambient temperatures.

MOTORCYCLE OIL 2T is recommended for 2-stroke motorcycles and scooters requiring JASO FB and/or ISO-L-EGB quality oil and is suitable for both oil-injection and premix lubrication systems. Always follow manufacturer's recommendation regarding oil to fuel ratio.

Typical Physical Characteristics

PROPERTY TEST	UNITS	METHODS	RESULT
Viscosity Grade	SAE J300		2-stroke
Colour		ASTM1500	Red L2.0
Density @ 15 °C	kg/m3		0.87
Kinematic Viscosity @ 40°C	cSt	ASTM D445	58.70
Kinematic Viscosity @ 100°C	cSt	ASTM D445	8.54
Viscosity Index		ASTM D2270	118

These characteristics are typical of current product methods whilst future production will conform to ENZOIL Lubricants specifications, variations in these physical characteristics may occur.

Health & Safety Environment

- This product is unlikely to present any significant health and safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.
- Avoid contact with eyes and skin, use proper impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Protect the Environment

- Take used oil to an authorized collection point. Do not discharge used or new oil into drains, soil or water.

***Unparalleled Reliability
Performance And Peace Of Mind***

