

MULTIGRADE ENGINE OIL EG5 20W50 API SL/CF

Products Data Sheet (PDS)

Product Description:

Pessenger car engine oil EG5 20W-50 is a high performance, mineral based, engine crankcase oil designed to provide outstanding lubrication across a broad range of both gasoline and light diesel engines. This premium engine oil is formulated for use all gasoline and diesel engines requiring a SAE 20W-50 multigrade engine oil. It exceeds the requirements of API Service Classifications SL/CF. It exceeds major car manufacturer's engine oil performance requirements for service fill and top-up purposes. It is formulated using low volatility base oils which contributes to reduced oil consumption. It contains a highly shear stable viscosity modifier to minimize viscosity change caused by changing temperatures.

EG5 20W-50 is recommended for use, under warranty conditions. Being an SAE 20W-50 multigrade oil it is suitable for use over a wide operating temperature range. Its high temperature stability, detergency and protection reserve keeps engine components clean and protected, thus reducing wear, ensuring long engine life over extended service intervals.

Typical Physical Characteristics

PROPERTY TEST	UNITS	METHODS	RESULT
Viscosity Grade	SAE J300		20W50
Colour		ASTM1500	L2.0
Density @ 15 °C	kg/m3		0.87
Kinematic Viscosity @ 40°C	cSt	ASTM D445	173.68
Kinematic Viscosity @ 100°C	cSt	ASTM D445	18.87
Viscosity Index		ASTM D2270	123

These characteristics are typical of current product methods whilst future production will conform to ENZOIL Lubricants specifications, variations in these physical characteristics may occur.

Health & Safety Environment

- This product is unlikely to present any significant health and safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.
- · Avoid contact with eyes and skin, use proper impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Protect the Environment

· Take used oil to an authorized collection point. Do not discharge used or new oil into drains, soil or water.

Unparalleled Reliability

Performance And Peace Of Mind

