

Product Description:

EXTREME PRESSURE 80W90 is an universal high performance mineral EP gear oil for use in manual transmission en transaxles of passenger cars, vans, light and heavy commercial vehicles, off-highway equipment, mining and agriculture where a SAE 80W90 GL-5 is been required.

EXTREME PRESSURE 80W90 is formulated with high refined mineral base stocks in combination with a special EP-additive technology to achieve the following performance:

- Good Extreme Pressure and Antiwear properties.
- High thermal- and oxidation stability.
- Effective rust, wear and corrosion protection.
- Better low temperature provides easy start-up at low ambient temperatures.
- Good anti-foam properties ensure film strength for effective lubrication.
- Excellent seal compatibility.

Typical Physical Characteristics

PROPERTY TEST	UNITS	METHODS	RESULT
Viscosity Grade	SAE J306		80W90
Colour		ASTM1500	L2.0
Density @ 15 °C	kg/m3		0.89
Kinematic Viscosity @ 40°C	cSt	ASTM D445	166.06
Kinematic Viscosity @ 100°C	cSt	ASTM D445	16.37
Viscosity Index		ASTM D2270	103

These characteristics are typical of current product methods whilst future production will conform to ENZOIL Lubricants specifications, variations in these physical characteristics may occur.

Health & Safety Environment

- This product is unlikely to present any significant health and safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.
- Avoid contact with eyes and skin, use proper impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Protect the Environment

- Take used oil to an authorized collection point. Do not discharge used or new oil into drains, soil or water.

***Unparalleled Reliability
Performance And Peace Of Mind***

