

MOTORCYCLE ENGINE OIL 4T 5W40 API SN JASO MA2

Products Data Sheet (PDS)

Product Description:

MOTORCYCLE OIL 4T 5W-40 is a premium quality fully synthetic lubricant especially developed for use in high powered 4-stroke motorcycles and is formulated from premium quality base stocks and high quality performance additives to exceed the most demanding lubrication requirements of modern 4-stroke motorcycles.

MOTORCYCLE OIL 4T 5W-40 provides excellent protection towards engine, gearbox and wet clutches used in 4-stroke motorcycles and ensures the highest possible reliability even under the most severe operating conditions.

MOTORCYCLE OIL 4T 5W-40 has superior thermo-oxidative stability, minimizing deposits and sludge formation. Exceptional anti-wear properties protect vital engine and gear components leading to lower maintenance costs. Controlled frictional properties eliminate clutch slippage, effectively improving the driveability of the vehicle. Outstanding low temperature properties enables easy starting at low ambient temperatures and ensures effective lubrication and wear protection at start up. MOTORCYCLE OIL 4T 5W-40 is recommended for a wide range of high powered 4-stroke motorcycles. MOTORCYCLE OIL 4T 5W-40 exceeds the specifications of API SN and JASO MA2 in addition to JASO MA as well as the requirements of leading global 4-stroke motorcycle manufacturers.

Typical Physical Characteristics

PROPERTY TEST	UNITS	METHODS	RESULT
Viscosity Grade	SAE J300		5W40
Colour		ASTM1500	L2.0
Density @ 15 °C	kg/m3		0.84
Kinematic Viscosity @ 40°C	cSt	ASTM D445	86.80
Kinematic Viscosity @ 100°C	cSt	ASTM D445	14.20
Viscosity Index		ASTM D2270	170

These characteristics are typical of current product methods whilst future production will conform to ENZOIL Lubricants specifications, variations in these physical characteristics may occur.

Health & Safety Environment

- This product is unlikely to present any significant health and safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.
- · Avoid contact with eyes and skin, use proper impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Protect the Environment

· Take used oil to an authorized collection point. Do not discharge used or new oil into drains, soil or water.

Unparalleled Reliability

Performance And Peace Of Mind

