

Product Description:

ATF MV is a high performance full synthetic, high quality automatic transmission fluid manufactured for multi-vehicle automatic transmissions. ATF MV is formulated with high quality additives that provide excellent friction durability and anti-shudder performance required by transmission manufacturers and meets the requirements of the major OEM commercial vehicle automatic transmission specifications. Full Synthetic Automatic Transmission Fluid is a technologically advanced, high viscosity formulation specially designed to deliver performance and maximum fuel efficiency for modern automatic transmissions. It is blended with premium synthetic base stocks, a balanced additive package and is fully approved by both GM for use in vehicles requiring their latest ATF specifications. In addition to approval from the two major US auto manufacturers, Full Synthetic Mutli-Vehicle ATF exceeds the requirements of the JASO-1A performance standard created by Japanese automobile manufacturers. This standard is recognized by Japanese OEM's in certifying ATF for use in their vehicles.

FULL SYNTHETIC DEXRON VI ATF is formulated to meet and exceed of more specifications, including OEMs manufacturer specifications or recommended oils:

JASO 1A performance	GM Dexron IIIG /H	Mitsubishi SP-III	Isuzu BESCO ATF-II / ATF-III
Aisin Warner JWS 3309	Allison C-3 & C-4	Nissan Matic C /D /J	Mazda ATF M-III /M-V
Chrysler ATF+,+3,+4	Honda ATF Z-1	Subaru /Suzuki ATF	MB 236.1 /236.2 /236.3 /236.5
Ford Mercon /Mercon V	Hyundai / Kia SP-III	Toyota T-III /T-IV	236.6 /236.7 /236.9

Typical Physical Characteristics

PROPERTY TEST	UNITS	METHODS	RESULT
Viscosity Grade			Dexron IIIH
Colour		ASTM1500	Red L5.0
Density @ 15 °C	kg/m3		0.84
Kinematic Viscosity @ 40°C	cSt	ASTM D445	37.23
Kinematic Viscosity @ 100°C	cSt	ASTM D445	7.48
Viscosity Index		ASTM D2270	173

These characteristics are typical of current product methods whilst future production will conform to ENZOIL Lubricants specifications, variations in these physical characteristics may occur.

Health & Safety Environment

- This product is unlikely to present any significant health and safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.
- Avoid contact with eyes and skin, use proper impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Protect the Environment

- Take used oil to an authorized collection point. Do not discharge used or new oil into drains, soil or water.

Unparalleled Reliability
Performance And Peace Of Mind

