

MOTORCYCLE ENGINE OIL 4T 10W40 API SN JASO MA2

Products Data Sheet (PDS)

Product Description:

MOTORCYCLE OIL 4T 10W-40 is a high quality parts synthetic lubricant especially developed for use in high powered 4-stroke motorcycles. MOTORCYCLE OIL 4T 10W-40 is formulated from premium quality synthetic base stocks and high quality performance additives to satisfy the demanding lubrication requirements of modern 4-stroke motorcycles.

MOTORCYCLE OIL 4T 10W-40 provides excellent protection towards engine, gearbox and wet clutches used in 4-stroke motorcycles and ensures the highest possible reliability even under the most severe operation conditions.

MOTORCYCLE OIL 4T 10W-40 has very good thermo-oxidative stability, minimising deposits and sludge formation. Exceptional anti-wear properties protect vital engine and gear components leading to lower maintenance costs. Controlled frictional properties eliminate clutch slippage, effectively improving the driveability of the vehicle. The good low temperature properties enable easy starting at low ambient temperatures and ensures effective lubrication and wear protection at start up.

MOTORCYCLE OIL 4T 10W-40 is recommended for a wide range of high powered 4-stroke motorcycles. MOTORCYCLE OIL 4T 10W-40 exceeds the specifications of API SN and JASO MA2 as well the requirements of many global 4-stroke motorcycle manufacturers.

Typical Physical Characteristics

PROPERTY TEST	UNITS	METHODS	RESULT
Viscosity Grade	SAE J300		10W40
Colour		ASTM1500	L2.0
Density @ 15 °C	kg/m3		0.85
Kinematic Viscosity @ 40°C	cSt	ASTM D445	98.93
Kinematic Viscosity @ 100°C	cSt	ASTM D445	14.58
Viscosity Index		ASTM D2270	153

These characteristics are typical of current product methods whilst future production will conform to ENZOIL Lubricants specifications, variations in these physical characteristics may occur.

Health & Safety Environment

- This product is unlikely to present any significant health and safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.
- · Avoid contact with eyes and skin, use proper impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Protect the Environment

· Take used oil to an authorized collection point. Do not discharge used or new oil into drains, soil or water.

Unparalleled Reliability

Performance And Peace Of Mind

