

Product Description:

FULL SYNTHETIC SYNature 5W40 engine oil is a premium quality full-synthetic, MID-SAPS engine oil designed to provide maximum protection for European passenger cars under all operating conditions. It also is recommended for other vehicles operating at extreme temperatures or under severe driving conditions, such as towing heavy loads. It is recommended for use in many gasoline and light-duty diesel engines. FULL SYNTHETIC SYNature 5W40 provides enhanced performance benefits compared with conventional engine oils. These benefits include better oxidation resistance and thermal stability at high temperatures for improved protection against viscosity breakdown and deposit formation; lower volatility for reduced oil consumption; and better low-temperature pumpability for easier starting and faster oil circulation at low temperatures. FULL SYNTHETIC SYNature 5W40 meets or exceeds the performance requirements of API Service Category SN/CF for the SAE 5W-40 viscosity and is approved for service fill under leading European OEM specifications. The SAE 5W-40 grade also is suitable for use in GM vehicles where the OEM specifies dexos2™ quality oil.

FULL SYNTHETIC SYNature 5W-40 is formulated to meet and exceed of more specifications, including OEMs manufacturer specifications or recommended oils:

ACEA C3-12
Porsche A40

VW 502.00/505.00
BMW Longlife-04

Renault RN0700/RN0710
MB-Approval 229.31/229.51

Typical Physical Characteristics

PROPERTY TEST	UNITS	METHODS	RESULT
Viscosity Grade	SAE J300		5W40
Colour		ASTM1500	L2.0
Density @ 15 °C	kg/m3		0.84
Kinematic Viscosity @ 40°C	cSt	ASTM D445	83.98
Kinematic Viscosity @ 100°C	cSt	ASTM D445	14.17
Viscosity Index		ASTM D2270	175

These characteristics are typical of current product methods whilst future production will conform to ENZOIL Lubricants specifications, variations in these physical characteristics may occur.

Health & Safety Environment

- This product is unlikely to present any significant health and safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.
- Avoid contact with eyes and skin, use proper impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Protect the Environment

- Take used oil to an authorized collection point. Do not discharge used or new oil into drains, soil or water.

**Unparalleled Reliability
Performance And Peace Of Mind**

